



Rost- und säurebest. härtpbarer gew. Rundstahl DIN 1013

09.11.2017

Abmessung mm	kg/m	Wn. 1.4057 V X20CrNi172	Wn. 1.4112 X90CrMoV18	Wn. 1.4122 V X39CrMo17-1		Abmessung mm
20 RD	2,48	●		●		20 RD
25 RD	3,90	●	●	●		25 RD
30 RD	5,58	●	●	●		30 RD
35 RD	7,60	●	●	●		35 RD
40 RD	9,93	●	●	●		40 RD
45 RD	12,57	●	●	●		45 RD
50 RD	15,51	●	●	●		50 RD
55 RD	18,77	●	●	●		55 RD
60 RD	22,34	●	●	●		60 RD
65 RD	26,21	●	●	●		65 RD
70 RD	30,40	●	●	●		70 RD
75 RD	34,90		●	●		75 RD
80 RD	39,71	●	●	●		80 RD
85 RD	44,83		●	●		85 RD
90 RD	50,28	●	●	●		90 RD
100 RD	62,04	●	●	●		100 RD
105 RD	68,40			●		105 RD
110 RD	75,07	●		●		110 RD
120 RD	89,34		●	●		120 RD
130 RD	104,86			●		130 RD
140 RD	121,61		●	●		140 RD
150 RD	139,60		●	●		150 RD
160 RD	158,83		●	●		160 RD
200 RD	248,18		●			200 RD