



Rost- und säurebest. blanker Rundstahl DIN 671

29.01.2018

Abmessung	kg/m	Wn. 1.4104	Wn. 1.4301	Wn. 1.4305	Wn. 1.4404	Wn. 1.4571	Abmessung
mm		X12CrMoS17	X5CrNi18-10	X10CrNiS189	X2CrNiMo17132	X6CrNiMoTi17-12	mm
2 RD	0,02			●			2 RD
2 RD	0,02		●			●	2 RD
3 RD	0,06		●	●		●	3 RD
4 RD	0,10		●	●		●	4 RD
5 RD	0,15	●	●	●		●	5 RD
6 RD	0,22	●	●	●	●	●	6 RD
7 RD	0,30		●	●		●	7 RD
8 RD	0,40	●	●	●	●	●	8 RD
9 RD	0,50		●	●		●	9 RD
10 RD	0,62	●	●	●	●	●	10 RD
11 RD	0,75			●			11 RD
12 RD	0,89	●	●	●	●	●	12 RD
13 RD	1,05		●	●		●	13 RD
14 RD	1,22	●	●	●		●	14 RD
15 RD	1,40	●	●	●	●	●	15 RD
16 RD	1,59	●	●	●		●	16 RD
17 RD	1,79		●	●			17 RD
18 RD	2,01	●	●	●		●	18 RD
20 RD	2,48	●	●	●	●	●	20 RD
22 RD	3,00	●	●	●		●	22 RD
24 RD	3,57	●	●	●		●	24 RD
25 RD	3,88	●	●	●	●	●	25 RD
26 RD	4,19		●	●		●	26 RD
27 RD	4,52		●	●			27 RD
28 RD	4,86		●	●		●	28 RD
30 RD	5,58	●	●	●	●	●	30 RD
32 RD	6,35	●	●	●		●	32 RD
35 RD	7,60	●	●	●		●	35 RD
36 RD	8,04		●	●			36 RD
38 RD	8,96			●		●	38 RD
40 RD	9,93	●	●	●	●	●	40 RD
42 RD	10,94			●			42 RD
45 RD	12,56	●	●	●	●	●	45 RD
50 RD	15,51	●	●	●	●	●	50 RD
55 RD	18,77			●		●	55 RD
60 RD	22,34	●	●	●	●	●	60 RD
2,50 RD	0,04		●	●			2,50 RD